

Anupam Enterprises

Protective Coatings Division

Wood Filler

Universal Wood / Grain Filler

Product Description

Wud-Fil wood filler has been designed to offer wood coating professionals an easy to use solvent based wood filler that can be applied on most variety of wooden surfaces and is very fast curing. It prepares a smooth surface for staining or finishing. It is recommended to be used on open grain timber, veneer etc. for interior / exterior furniture. No sanding is required and the excess filler can be easily wiped off the surface with a clean fabric.

Features and Benefits

- Thixotropic consistency and can be applied by cotton pad or rag.
- Single package product for ease in application.
- Available in natural colour but can be tinted with either pigments and solvent based wood stains.
- Cures very rapidly and can be sanded after 30 minutes of application.
- Provides a smooth, uniform surface.
- Takes stains well, has excellent adhesion with stains.
- Recommended for both interior / exterior furniture.
- Can be successfully overcoated with **Anuthane Enamel, Monocoat Enamel, Anu-Min, Anuthane - 301**, Nitro Cellulose, acrylic, vinyl, alkyd and latex wood lacquers.

TECHNICAL DATA

Name/Description	Wud-Fil
Type	Single pack cold curing
Composition	Special Resin / Fillers
Colour	Natural
Finish	Smooth Matt
Serviceability @ 30° C	
- Dry to touch	5-10 minutes
- Sanding	Generally not required. But can be sanded after 15-20 minutes.
- Re-coat	30 minutes
Flash Point	15° C
Solvent/Thinner	Xylene / Toluene
Precaution	Flammable. Keep away from heat and open flame. Maintain good ventilation and avoid breathing vapours.
Packing	1 kg. & 5 kgs.
Shelf Life	12 months

Application:

All wooden surfaces must be dry and sanded smooth with 220 or finer grit sandpaper along the grain of the wood before applying filler. Remove dust using tack rag or vacuum cleaner. Stir well and dilute the filler with recommended solvent to obtain desired application properties. Use cotton pad or rag to apply with circular motion around areas to be filled. Wipe excess filler off the surface with a clean fabric. Allow 20-30 minutes before application of any sealer / topcoat.

Disclaimer:

Information provided herein is based upon tests believed to be reliable. It does not guarantee the results to be obtained. Nor does it make any express and implied warranty or merchantability, or fitness for a particular purpose concerning the effects or results of such case. It does not release you from the obligation to test the products supplied by us as to their suitability for the intended uses. The application, surface preparation and use of the products are beyond our control and, therefore, entirely your own responsibility.

Anupam Enterprises

Protective Coatings Division

" Poddar Point "
113 Park Street
Block - B, 5th Floor
Calcutta - 700 016
West Bengal, India

Phone: +91-33-216 1204 & 216 1205
Fax: +91-33-216 1227 & 238 9823
E-Mail: anupam@cal.vsnl.net.in
Website: www.anupampaints.com